

# Sky Factory eScape™ 2.0 Digital Cinema

## DC-eScape-4123 Specifications

### Monitor:

49" (1245mm) Professional LED Edgelit LCD Monitor  
Resolution: 1920 x 1080

### Mounting Pan with Integrated Video-Audio Playback Equipment:

#### Mounting Pan

16 gauge steel, powder coated silver  
Provides one location for all playback equipment  
Protects eScape monitor and video-audio playback equipment, facilitates wiring, and provides ventilation for proper cooling  
Rough opening: call the Sky Factory for specific requirements.  
Requires wire access from top during rough-in for power, signal cable to controller, and audio cable  
Junction box with 1/2" (22mm) trade size knock-outs; where conduit is specified, flexible will be required  
Video-audio playback equipment  
Simple plug-in module for additional content

### Wall Mounted Controller

Wired via Cat 6 cable  
Simple illuminated push button operation  
Fits in single gang outlet box  
Low voltage mounting bracket provided  
Keypad bezel available in white, almond or black  
Standard Decora style faceplate available in white, almond, black or stainless steel  
Other faceplate options available from Leviton

### Speakers

Two 2-way speakers  
5.25" (133mm) dia. woofer, 0.5" (13mm) tweeter  
7.95" (202mm) dia. trim ring comes in white, can be painted  
6.625" (168mm) dia. rough opening, 3.2" (80mm) mounting depth  
Tile bridge and backcan enclosure for drop ceiling applications  
Backcan is UL Listed for air handling spaces  
2.26 lbs (1.03kg)

### Cabling:

One plenum rated Cat 6 cable  
Monitor location to wall mounted controller  
Ends terminated with RJ45 connectors  
35' (15.3m) standard, alternate lengths available if specified  
Plenum rated speaker cable  
monitor location to speaker locations  
70' (30.6m) standard, or 35' (15.3m) +/- per speaker (alternate lengths available if specified)

### Trim:

Wood or brushed anodized clear or black aluminum (style and material selected by client)  
Sizes vary with style and material selection  
30 1/2" (775mm) to 33" (838mm) wide  
49 1/16" (1246mm) to 52 1/16" (1333mm) high  
7/16" (11mm) to 2" (51mm) deep from wall surface

### Electrical Requirements:

Input: 100-240V AC, 50-60Hz  
Total Power Consumption: 184 Watts  
Circuit Recommendations: a separate circuit is advisable  
Power Surge Protection: recommended, but not provided  
Operating Temperature: 32F ~ 94F (0C ~ 40C)  
Operating Humidity: 10% ~ 80 % non-condensing

### Fixture Weight:

76.8 lbs + 10.1 to 28.9 lbs depending on trim choice  
(34.9kg + 4.6 to 13.1kg depending on trim choice)

eScape™

Recessed Wall Mount  
High-Definition (HD)  
Digital Cinema Virtual Window



### Viewable Area:

approx. 41" x 23" (1041mm x 584mm)  
depending on trim selection

### Video Content (provided):

8, 12 or 16 hours of full HD Resolution (1920 x 1080) videos  
Recorded in Ultra HD  
Mastered and played back in high bit-rate Full HD  
More footage capacity available in the future  
Simple plug-in module for additional content

**Notice: This product is NOT compatible with MRI and high energy particle imaging environments, such as Linac.**

### Warranty:

2 year Sky Factory, Inc. limited warranty on entire system

**This document specifies product only.  
For rough opening and installation specifications,  
call the Sky Factory.**